PERFORMER EVO

FARM HARD

firestone





BRIDGESTONE AMERICAS TIRE OPERATIONS, LLC AGRICULTURAL TIRE DIVISION



PERFORMER EVO



INTRODUCING

PERFORMER EVO RADIAL TIRES

Not every tractor works 5,000 acres of row crops or has to withstand miles of chopped corn stalks. But, you still want quality rubber on all of your equipment. Performer EVO tires are our way to deliver that. It doesn't matter if you're hauling hay, picking rocks, or spreading manure. If you need a job done well, you need a Firestone.







THE OTHER GUY

A secondary tractor doesn't always require top-of-the-line tires. But, if you still want Firestone quality on it, Performer EVO is right for you.



THE LIVESTOCK & DAIRY

If you use your machines mostly for hauling feed or light traveling back and forth between buildings, Performer EVO is the right choice.



THE TRADE-UP

Radial tires offer significant advantages over bias tires, such as reduced inflation pressures and increased sidewall flexion. Performer EVO is a prime candidate if you're looking to trade up from bias.

PERFORMER EVO ADVANTAGE

FIRESTONE-TESTED

6-YEAR LIMITED
WARRANTY*

FOR LONGER WEAR



 * Certain restrictions and limitations apply. See firestoneag.com for details.

PERFORMER EVO

Performer EVO is a new line of Firestone tires created to suit the needs of more farmers. If you've got a tractor that needs a dependable tire, there's a Firestone for you.

Material Description	Full Size	Load Index	Speed Rating	Design Rim Width
Performer EVO	380/85R24	131	D	12.00
Performer EVO	340/85R28	127	D	11.00
Performer EVO	380/85R28	133	D	12.00
Performer EVO†	420/85R28	139	D	13.00
Performer EVO†	380/85R30	135	D	12.00
Performer EVO†	420/85R30	140	D	13.00
Performer EVO	460/85R30	145	D	15.00
Performer EVO†	420/90R30	145	D	13.00
Performer EVO†	380/85R34	137	D	12.00
Performer EVO	420/85R34	142	D	13.00
Performer EVO	460/85R34	150	D	15.00
Performer EVO†	400/75R38	138	D	13.00
Performer EVO	420/85R38	144	D	13.00
Performer EVO	460/85R38	149	D	15.00
Performer EVO 23°†	480/80R42	156	D	15.00
Performer EVO 23°†	480/80R46	158	D	15.00



PERFORMER EVO PERFORMER EVO 23°

Overall Diameter (in.)	Overall Width (in.)	Bar Height (in.)	Max Load and Inflation (LBS @ PSI)
49.2	15.3	1.8	4300 @ 23
50.5	13.5	1.9	3860 @ 23
53.2	15.3	1.9	4540 @ 23
55.7	17.0	2.0	5360 @ 23
55.5	15.3	1.8	4800 @ 23
58.3	16.8	2.0	5520 @ 23
60.5	18.3	2.1	6400 @ 23
59.6	16.7	2.1	6400 @ 29
59.1	15.1	1.8	5080 @ 23
61.9	16.8	2.0	5840 @ 23
64.5	18.3	2.1	7400 @ 29
61.7	15.5	1.9	5200 @ 23
65.9	16.8	2.0	6150 @ 23
68.5	18.3	2.1	7150 @ 23
73.0	19.3	1.8	8800 @ 35
76.2	19.1	1.8	9350 @ 35

